Keren

New-generation radiant panel heater equipped with self-programming features and integrated optimiser

MODEL DEPOSIT EUROPE
PROTECTED DESIGN
MODEL DEPOSIT EUROPE

Also available...
in a connected version **Estyle**

Keren
online

DEVELOPED
DESIGNED AND
MANUFACTURED
FRANCE

Warranty 3 years
3 years warranty

Maintenance free

Radiant heat

PID technology

Low energy consumption

Benefits

+ Radiated gentle heat, uniformity, and optimal comfort.
+ Significantly improved ergonomics, and enhanced readability thanks to the large negative backlit LCD display (black background with white digits).
+ Made in France at our Pont-Evêque site (dpt38): optimised airflow and temperature measurement.
+ Intuitive digital control panel with lockable features, large backlit display, and integrated occupancy detector.
+ High level of repairability, with most components interchangeable, for example the controller with integrated sensor without having to dismantle the device.
+ EcoSens® innovation pack: Occupancy detection, automatic self-learning or manual weekly programming, dual optimisation feature.
+ Open window detection, gauge, and power consumption indication, setting temperature limitation, keypad lock and by PIN code, 7-day, and daily programme.
+ 100% recyclable packaging made from cardboard and cellulose wadding (zero plastic, zero polystyrene).

Technical specifications

- Two-tone bodywork in epoxy-painted sheet steel, finished in satin white or anthracite grey on the front and dark grey on the rear.
- Mounted on lockable steel wall bracket which serves as a drilling template.
- PID (Proportional Integral Derivative) control by triac.
- Permanent backup in case the mains power supply goes off (date and time is saved for up until 16 hours).
- Overheating protection.
- 6-order pilot wire compatible with energy programmer.
- Manufactured in France on NF certified site.
- IP24, class II.

CE
UK CA

References		Powers (W)	Heights (mm)	Widths (mm)	Depths* (mm)	Gross weight (Kg)
White version	Anthracite version					
RH0501A	**RH0501ANA**	500	470	450	95	5,8
RH0751A	**RH0751ANA**	750	470	547	95	6,7
RH1001A	**RH1001ANA**	1000	470	618	95	7,6
RH1251A	**RH1251ANA**	1250	470	763	95	9,2
RH1501A	**RH1501ANA**	1500	470	838	95	10
RH1751A	**RH1751ANA**	1750	470	993	95	11,5
RH2001A	**RH2001ANA**	2000	470	1058	95	12,4

** For the depth of Keren installed, add 35 mm to the value of its depth.*

Help for the visually impaired

Child anti-tamper